




**Hart-Lock™
Industrial Grade
Locking Devices**3-Pole, 3-Wire Non-Grounding
10A, 250V/AC; 15A, 125V/AC
Non-NEMA

4755



7567N



7580

Industrial Grade Plugs & Connectors

Rating A	V/AC	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	
10/15	125/250	SafetyGrip Straight Body	0.33-0.66" (8.4-16.7mm)	BK & W	<input type="checkbox"/> 4767	—	•
		SafetyGrip Straight Body	0.33-0.66" (8.4-16.7mm)	BK & W	—	<input type="checkbox"/> 4755	•
		SafetyGrip Angled Body	0.33-0.66" (8.4-16.7mm)	BK & W	<input type="checkbox"/> 4767AN	—	•
		AutoGrip Straight Body	0.33-0.66" (8.4-16.7mm)	BK & W	<input type="checkbox"/> 7567N	<input type="checkbox"/> 7565N	

Industrial Grade Receptacles

Rating A	V/AC	Description	Color	Single Receptacle	Duplex Receptacle	
10/15	125/250	Standard Industrial	BK	<input type="checkbox"/> 7582	<input type="checkbox"/> 7580	

Accessories for Non-NEMA 10/15A Locking Devices

Description	Catalog No.	
Neoprene weather protective boot for 10/15A plug	<input type="checkbox"/> BS1	
Neoprene weather protective boot for 10/15A connector	<input type="checkbox"/> BS2	
Diecast aluminum single receptacle cover, vertical mount, for FS/FD Boxes	<input type="checkbox"/> 7420	•
Glass filled nylon flanged inlet/outlet cover, vertical mount, for 10/15A devices	<input type="checkbox"/> WP1	•



BS1



BS2



7420



WP1

Complex Environment (D)See Section D for Watertight,
Severe-Duty & Corrosion
Resistant Devices**Dimensional Information:**
C-76-C-78**Plug & Connector Specification****Information:**
SafetyGrip Non-NEMA 10/15A:
C-84Auto Grip Non-NEMA 10/15A:
C-84**Receptacle Specification**
Information:
Non-NEMA 10/15A: C-86**Color Information:**
BK (Black), W (White)**Specifications and availability are subject to change without notice.**

Indicates NAFTA Compliant - Page R-30