


**Hart-Lock™
Complex Environment
Locking Devices**

3-Pole, 3-Wire Non-Grounding
30A, 3Ø 250V/AC
NEMA L11-30




Hart-Lock 3Ø Plugs & Connectors <small>c(UL)us</small> <small>NOM 426</small>							
Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.
30	250	L11-30	3Ø Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1130PW	□ L1130CW
			3Ø Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1130PWBK	□ L1130CWBK
			3Ø Severe Duty	0.38-1.00" (9.5-25.4mm)	Y & BK	□ L1130PY	□ L1130CY



L1130PY

Hart-Lock 3Ø Receptacles <small>c(UL)us</small> <small>NOM 426</small>					
Rating A	V/AC	NEMA	Description	Color	Single Receptacle Catalog No.
30	250	L11-30	3Ø Watertight	Y	□ L1130RW
			3Ø Watertight	BK	□ L1130RWBK



L1420CW

**Hart-Lock™
Complex Environment
Locking Devices**

3-Pole, 4-Wire Grounding
20A, 125/250V/AC
NEMA L14-20



Hart-Lock Plugs & Connectors <small>c(UL)us</small> <small>NOM 426</small>							
Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.
20	125/ 250	L14-20	Watertight	0.36-0.84" (9.1-21.3mm)	Y	□ L1420PW	□ L1420CW
			Watertight	0.36-0.84" (9.1-21.3mm)	BK	□ L1420PWBK	□ L1420CWBK
			Severe Duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1420PY	□ L1420CY
			SafetyGrip Corrosion Resistant	0.38-1.00" (9.5-25.4mm)	Y	□ CRL1420P	□ CRL1420C

Hart-Lock Receptacles <small>c(UL)us</small> <small>NOM 426</small>					
Rating A	V/AC	NEMA	Description	Color	Single Receptacle Catalog No.
20	125/ 250	L14-20	Watertight	Y	□ L1420RW
			Watertight	BK	□ L1420RWBK
			Corrosion Resistant	Y	□ CRL1420R*

* Only UL, CSA, Fed Spec and NOM certified

Color Information:

Colors: BK (Black), Y (Yellow)



Specifications and availability are subject to change without notice.

Indicates NAFTA Compliant - Page R-30

Dimensional Information: D-33

Specification Information:
Watertight Industrial Plugs & Connectors: D-36
Watertight Industrial Receptacles: D-37
Severe Duty Industrial Plugs & Connectors: D-38
Corrosion Resistant: D-39