




Performance Data

Unit #	WA412YRE	WA418ZRX	WA425ZREB
BTU Cooling	12000	18500 / 18200	24700 / 25000
BTU Heating	none	none	none
SEER	11.3	9.7	9.8
Dehumidification / (pints/hour)	2.5	3.3	5.7
Airflow (CFM)	288/244/206	441/394/353	523/485/445
Voltage	115	230/208	208/230
Frequency/cycle	60 Hz	60 Hz	60 Hz
AMPS Cooling	9.5	8.4 / 9.1	12.4 / 11.3
AMPS Heating	na	na	na
Watts Cooling	1378	1907 / 1876	2520 / 2551
Watts Heating	na	na	na
Plug Type	 5-15P 5-15R	 6-15P 6-15R	 6-20P 6-20R
Controls	Remote	Remote	Remote
Operating Range	62° to 86°F	64° to 109°F	64° to 109°F
Cabinet Size (inches)			
Width	19	23 5/8	26 1/2
Depth	21 1/2	25 1/2	26 1/2
Height	14 3/5	17 3/16	18 3/5
Window Opening (inches)	23 - 36	26 1/2 - 40 1/2	31 - 42
Thru-Wall Max Thickness	8	10	10
Weight (pounds)	69 / 76.6	121.3 / 103	129.8 / 145.4
Power Cord Rating/amps	15	15	20
Power Cord Type	LCDI	LCDI	LCDI
Power Cord Length	78"	78 3/4"	69"
Refrigerant	R410A	R410A	R410A
Refrigerant Charge/oz.	20.11	23.28	36.7
Sound (indoor/outdoor) dba	61 / 67	60.5 / 55.8	63.2 / 68.2
4 Way Air Adjustment	yes	yes	yes
2 Way Air Swing	yes	yes	yes
Air Discharge	Top Front	Top Front	Top Front
Motor Type	Ball Bearing	Ball Bearing	Ball Bearing
Motor Capacitor	15 µF	8 µF	8 µF

